## CED 1911 Toolkit

The CED 1911 Toolkit is designed to provide the necessary tools to completely disassemble Colt 1911 and many similar style guns, such as Springfield, Para-Ordnance, Kimber, Auto Ordnance, and others. The CED 1911 Toolkit will also handle many of the "after market" accessories used on these guns including extended magazine catches, adjustable rear sights, and recoil spring guide rods.

Guns are expensive items, and most owners take pride in their appearance. Nothing will ruin the appearance quicker than screws damaged by ill-fitting screwdrivers. The CED 1911 Toolkit has the optimum sized tool blades, hollow ground to preserve the appearance of the screw whilst providing maximum torque to remove even the most stubborn screw.

The handle of the CED 1911 Toolkit houses six uniquely different precision crafted tool blades, which remain secure in the handle at all times and therefore cannot be lost! Each tool arm locks into position in the center of the handle providing almost 3 inches of unobstructed view and working clearance.

The function of each tool bit is as follows:

	Tool	Use
	5/32" Pin Punch	Remove and install the firing pin.
1		Remove and install the Mainspring housing retaining pin.
		Remove the hammer axis pin.
		Remove Magazine base pads
	Small Screwdriver	Remove and install the magazine catch.
2	.150"	Some sight adjusting screws such as the windage screw on the Gold Cup rear sight.
	Medium Screwdriver	Fits the adjusting screws on most rear sights including Bo-mar, LPA, Millett*, and Gold Cup*
3	.210"	
	Large Screwdriver	For grip screws.
4	.325"	Note: We found that there were two distinct widths of grip screws on the market. Some have slots
		around .039" wide, while others .050". Unfortunately, we could not accommodate both with a
		perfectly sized blade, so we have used the smaller size.
	3/32" Hex Drive	Fits most extension buttons screwed onto magazine catches and aftermarket grip screws with hex
5		heads.
		Can also be used to push out the sear axis pin and depressing the detent to fit the safety catch.
	5/32" Hex Drive	Fits several brands of two piece recoil spring guide rods.
6		

<sup>\*</sup> The windage screws of the Millet and the Gold Cup may be too narrow for this blade. In such cases, use the small screwdriver blade for this adjustment.